



DRIP IRRIGATION FITTINGS
MINI VALVES

DRIP IRRIGATION FITTINGS

MINI VALVES



OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate the water flow from sealing rubber inserted outlet to thin wall dripline

Product code	Size	Bag quantity	Box quantity	Box weight
016 VOY C14 000 Y16	14 x 16 mm	50	250	6,4 kg
016 VOY C16 000 Y16	16 x 16 mm	50	250	6,6 kg
022 VOY C20 000 Y22	20 x 22 mm	25	150	6,7 kg
025 VOY C25 000 Y25	25 x 25 mm	25	125	7,4 kg



OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from sealing rubber inserted outlet to thin/medium wall dripline

016 VOS C14 000 S16	14 x 16 mm	50	250	6,9 kg
016 VOS C16 000 S16	16 x 16 mm	50	250	7 kg
020 VOS C20 000 S20	20 x 20 mm	25	150	6,5 kg
022 VOS C20 000 S22	20 x 22 mm	25	150	6,7 kg
025 VOS C25 000 S25	25 x 25 mm	25	125	7,9 kg



BARBED OFFTAKE MINI VALVE

Used to turn off or regulate the water flow from sealing rubber inserted outlet to thick wall dripline

016 VOK C16 000 K16	16 x 16 mm	50	250	5,7 kg
020 VOK C20 000 K20	20 x 20 mm	25	150	5,7 kg



SELF-SEAL BARBED OFFTAKE MINI VALVE

Used to turn off or regulate the water flow from outlet w/o sealing rubber to thick wall dripline

016 VCK C16 D17 K16	16 x 16 mm	50	250	6,3 kg
---------------------	------------	----	-----	--------



BARBED MINI VALVE WITH NUT

Used to turn off or regulate the water flow from thick walled dripline to thin/medium wall dripline

016 VSK K16 000 S16	16 x 16 mm	50	250	6,2 kg
020 VSK K20 000 S20	20 x 20 mm	25	150	6,4 kg
022 VSK K20 000 S22	20 x 22 mm	25	150	6,6 kg
025 VSK K25 000 S25	25 x 25 mm	25	100	6,6 kg



BARBED MINI VALVE

Used to turn off or regulate the water flow between thick wall driplines

016 VKK K16 000 K16	16 x 16 mm	50	250	5,4 kg
020 VKK K20 000 K20	20 x 20 mm	25	150	5,5 kg

DRIP IRRIGATION FITTINGS

MINI VALVES



MALE THREADED OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from female threaded outlet to thin/medium wall dripline

Product code	Size	Bag quantity	Box quantity	Box weight
016 VSM M03 000 S16	16 mm x 1/2"	50	250	7,7 kg
020 VSM M04 000 S20	20 mm x 3/4"	25	150	7,2 kg
022 VSM M04 000 S22	22 mm x 3/4"	25	150	7,1 kg



FEMALE THREADED OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate the water flow from female threaded outlet to thin wall dripline

016 VYF F03 000 Y16	16 mm x 1/2"	50	250	6,7 kg
---------------------	--------------	----	-----	--------



FEMALE THREADED OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from male threaded outlet to thin/medium wall dripline

016 VSF F03 000 S16	16 mm x 1/2"	50	250	7,3 kg
---------------------	--------------	----	-----	--------



COMPRESSION OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from outlet w/o sealing rubber to thin/medium wall dripline

016 VOS D08 N06 S16	8 x 16 mm	50	250	7,7 kg
---------------------	-----------	----	-----	--------



LAY FLAT OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from lay flat main pipe to thin/medium wall dripline

016 VOL X13 000 S16	13 x 16 mm	50	150	7,1 kg
016 VOL X18 000 S16	18 x 16 mm	50	150	7,1 kg
020 VOL X13 000 S20	13 x 20 mm	25	100	6,9 kg
020 VOL X18 000 S20	18 x 20 mm	25	100	6,9 kg
022 VOL X13 000 S22	13 x 22 mm	25	100	6,9 kg
022 VOL X18 000 S22	18 x 22 mm	25	100	6,9 kg



LAY FLAT SPIRAL OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate the water flow from lay flat main pipe to thin/medium wall dripline

016 VOL U16 000 S16	16 x 16 mm	50	150	7,1 kg
020 VOL U16 000 S20	16 x 20 mm	25	100	6,9 kg
022 VOL U16 000 S22	16 x 22 mm	25	100	6,9 kg



LAY FLAT OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate the water flow from lay flat main pipe to thin wall dripline

016 VOP X13 000 Y16	13 x 16 mm	50	200	6,5 kg
016 VOP X18 000 Y16	18 x 16 mm	50	200	6,5 kg

DRIP IRRIGATION FITTINGS

MINI VALVES



LAY FLAT SPIRAL OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate the water flow from lay flat main pipe to thin wall dripline

Product code	Size	Bag quantity	Box quantity	Box weight
016 VOP U16 000 Y16	16 x 16 mm	50	200	6,4 kg



LAY FLAT OFFTAKE MINI VALVE WITH NUT (ECO)

Used to turn off or regulate the water flow from lay flat main pipe to thin/medium wall dripline

016 VOP X13 000 S16	13 x 16 mm	50	200	6,8 kg
016 VOP X18 000 S16	18 x 16 mm	50	200	6,8 kg



LAY FLAT SPIRAL OFFTAKE MINI VALVE WITH NUT (ECO)

Used to turn off or regulate the water flow from lay flat main pipe to thin/medium wall dripline§

016 VOP U16 000 S16	16 x 16 mm	50	200	6,7 kg
---------------------	------------	----	-----	--------



MALE THREADED MINI VALVE

Provides a turn off or water regulation with a combination of male threads

016 VMM M03 000 M03	16 mm x ½"	50	250	6,5 kg
016 VMM M04 000 M04	16 mm x ¾"	25	200	6,1 kg
020 VMM M04 000 M04	20 mm x ¾"	25	150	6,7 kg



MALE THREADED LOCK TYPE OFFTAKE MINI VALVE

Used to turn off or regulate the water flow from female threaded outlets to medium/thick wall driplines

016 VMG M03 000 G16	16 mm x ½"	25	200	7,4 kg
016 VMG M04 000 G16	16 mm x ¾"	25	175	7,4 kg
020 VMG M04 000 G20	20 mm x ¾"	25	125	7,1 kg



LOCK TYPE MINI VALVE

Used to turn off or regulate the water flow between medium/thick wall driplines

016 VGG G16 000 G16	16 x 16 mm	25	150	7,3 kg
020 VGG G20 000 G20	20 x 20 mm	25	100	7 kg



LOCK TYPE REDUCTION MINI VALVE

Used to turn off or regulate the water flow between medium/thick wall driplines of different sizes

020 VGG G20 000 G16	20 x 16 mm	25	100	6,4 kg
---------------------	------------	----	-----	--------

DRIP IRRIGATION FITTINGS

MINI VALVES



TEE OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate 2-way water flow from sealing rubber inserted outlet to thin wall driplines

Product code	Size	Bag quantity	Box quantity	Box weight
016 VTY Y16 C16 Y16	16 x 16 mm	25	125	6,1 kg
022 VTY Y22 C20 Y22	20 x 22 mm	25	100	5,9 kg



TEE OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate 2-way water flow from sealing rubber inserted outlet to thin/medium wall driplines

016 VTS S16 C16 S16	16 x 16 mm	25	125	6,6 kg
022 VTS S22 C20 S22	20 x 22 mm	25	100	6,1 kg



TEE MINI VALVE WITH RING

Used to turn off or regulate 2-way water flow between thin wall driplines

016 VTY Y16 Y16 Y16	16 x 16 mm	25	125	6,3 kg
---------------------	------------	----	-----	--------



TEE MINI VALVE WITH NUT

Used to turn off or regulate 2-way water flow between thin/medium walled driplines

016 VTS S16 S16 S16	16 x 16 mm	25	125	7 kg
---------------------	------------	----	-----	------



MALE THREADED TEE OFFTAKE MINI VALVE WITH RING

Used to turn off or regulate 2-way water flow from female threaded outlet to thin wall driplines

016 VTY Y16 M03 Y16	16 mm x 1/2"	25	125	6,2 kg
022 VTY Y22 M03 Y22	22 mm x 1/2"	25	100	6 kg



MALE THREADED TEE OFFTAKE MINI VALVE WITH NUT

Used to turn off or regulate 2-way water flow from female threaded outlet to thin/medium wall driplines

016 VTS S16 M03 S16	16 mm x 1/2"	25	125	6,6 kg
022 VTS S22 M03 S22	22 mm x 1/2"	25	100	6,1 kg



HEADQUARTERS

Orhan Gazi Mah. Isiso San. Sit.
15. Yol Y Blok No: 33 34538
Esenyurt, İstanbul, Turkey
+90 212 623 23 08

FACTORY

Organize Sanayi Bölgesi Bursa
Karayolu 6. km. 2. Cd. No: 2
Çanakkale, Turkey
+90 286 214 32 07

Website www.sunstream.com.tr | **Support** info@sunstream.com.tr

© 2022 İSKO Plastik ve Kalıp San. Tic. A.Ş.